

Supplier	TOSHIBA CARRIER CORPORATION
----------	-----------------------------

Indoor unit	RAS-B10J2KVG-E
-------------	----------------

Indoor unit	RAS-B10J2KVG-E
-------------	----------------

Outdoor unit	RAS-2M14U2AVG-E
--------------	-----------------

Sound power level

indoor unit (cooling)	dB	54
-----------------------	----	----

outdoor unit (cooling)	dB	58
------------------------	----	----

indoor unit (heating)	dB	54
-----------------------	----	----

outdoor unit (heating)	dB	59
------------------------	----	----

Refrigerant

Type		R32
------	--	-----

Global Warming Potential	kgCO ₂ eq	675
--------------------------	----------------------	-----

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

Energy efficiency class		A++
-------------------------	--	-----

Design load (P _{designc})	kW	4,00
-------------------------------------	----	------

Seasonal efficiency (SEER)		6,54
----------------------------	--	------

Seasonal electricity consumption (Q _{CE})	kWh/annum	214
---	-----------	-----

Heating

		Heating/Average	Heating/Warmer	Heating/Colder
Energy efficiency class		A+	—	—
Design load (Pdesignh)	kW	3,10	—	—
Seasonal efficiency (SCOP)		4,54	—	—
Seasonal electricity consumption (Q _{HE})	kWh/annum	956	—	—
Back up heating capacity	kW	0,73		
Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j.				
T _j = -7°C (Pdh)	kW	2,74	-	—
T _j = 2°C (Pdh)	kW	1,67	—	—
T _j = 7°C (Pdh)	kW	1,95	—	—
T _j = 12°C (Pdh)	kW	2,28	—	—
T _j =bivalent temperature (Pdh)	kW	2,74	—	—
T _j =operation limit (Pdh)	kW	1,14	—	—
T _j = -15°C (Pdh)	kW	-	-	—