

| | |
|----------|-----------------------------|
| Supplier | TOSHIBA CARRIER CORPORATION |
|----------|-----------------------------|

| | |
|--------------|-----------------|
| Indoor unit | RAS-B10J2KVG-E |
| Indoor unit | RAS-B10J2KVG-E |
| Indoor unit | RAS-B10J2KVG-E |
| Indoor unit | RAS-B10J2KVG-E |
| Outdoor unit | RAS-4M27U2AVG-E |

Sound power level

| | | |
|------------------------|----|----|
| indoor unit (cooling) | dB | 54 |
| outdoor unit (cooling) | dB | 63 |
| indoor unit (heating) | dB | 54 |
| outdoor unit (heating) | dB | 64 |

Refrigerant

| | | |
|--------------------------|----------------------|-----|
| Type | | R32 |
| Global Warming Potential | kgCO ₂ eq | 675 |

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling

| | | |
|---|-----------|------|
| Energy efficiency class | | A+ |
| Design load (P _{designc}) | kW | 7,90 |
| Seasonal efficiency (SEER) | | 6,02 |
| Seasonal electricity consumption (Q _{CE}) | kWh/annum | 459 |

Heating

| | | Heating/Average | Heating/Warmer | Heating/Colder |
|---|-----------|-----------------|----------------|----------------|
| Energy efficiency class | | A+ | — | — |
| Design load (Pdesignh) | kW | 5,20 | — | — |
| Seasonal efficiency (SCOP) | | 4,25 | — | — |
| Seasonal electricity consumption (Q _{HE}) | kWh/annum | 1712 | — | — |
| Back up heating capacity | kW | 1,22 | | |
| Declared capacity for heating, at indoor temperature 20°C and outdoor temperature T_j. | | | | |
| T _j = -7°C (Pdh) | kW | 4,60 | - | — |
| T _j = 2°C (Pdh) | kW | 2,80 | — | — |
| T _j = 7°C (Pdh) | kW | 2,92 | — | — |
| T _j = 12°C (Pdh) | kW | 3,59 | — | — |
| T _j =bivalent temperature (Pdh) | kW | 4,60 | — | — |
| T _j =operation limit (Pdh) | kW | 2,94 | — | — |
| T _j = -15°C (Pdh) | kW | - | - | — |